

AD-A134 234


A COMPILATION OF MOORED CURRENT METER DATA FROM THE  
WESTERN NORTH PACIFIC. (U) WOODS HOLE OCEANOGRAPHIC  
INSTITUTION MA E LEVY ET AL. AUG 83 WHOI-83-30  
N00014-76-C-0197


1/1

UNCLASSIFIED

F/G 8/3

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

1 1 1 1  
H E E E

5072-  
REPC

4. TIR  
A C  
No

7. Aut  
ELL

9. Per  
Wo  
Wo

12. Se  
Of  
Wa

15. Sh  
Thi

16. As

me  
plo  
tive  
The  
var

17. O  
1.  
2.  
3.

<b>REPORT DOCUMENTATION PAGE</b>	<b>1. REPORT NO.</b> WHOI-83-30	<b>2.</b>	<b>3. Recipient's Accession No.</b>
<b>4. Title and Subtitle</b> A Compilation Of Moored Current Meter Data From The Western North Pacific, Volume XXXI, 1980 - 1982			<b>5. Report Date</b> August 1983
<b>7. Author(s)</b> Ellen Levy and Susan A. Tarbell			<b>8. Performing Organization Rept. No.</b> WHOI-83-30
<b>9. Performing Organization Name and Address</b> Woods Hole Oceanographic Institution Woods Hole, Massachusetts 02543			<b>10. Project/Task/Work Unit No.</b>
<b>12. Sponsoring Organization Name and Address</b> Office of Naval Research Washington, DC			<b>11. Contract(C) or Grant(G) No.</b> (C) N00014-76-C-0197; (G) NR 083-400
			<b>13. Type of Report &amp; Period Covered</b> Technical
<b>15. Supplementary Notes</b> This report should be cited as: Woods Hole Oceanog. Inst. Tech. Rept. WHOI-83-30.			<b>14.</b>
<b>16. Abstract (Limit: 200 words)</b>  Summaries of long-term current, temperature and pressure measurements from moored instruments in the western Pacific Ocean (along 152°E, between 28°N and 41°N) are presented. Tables, plots, and statistics are presented for filtered and unfiltered time series. There were two consecutive settings of instruments, referred to as WesPac I and II, each spanning a one year interval (nominal). The objective of the experiment was to motivate exploratory descriptions of the low frequency variability in the western North Pacific.			
<b>17. Document Analysis a. Descriptors</b> 1. Pacific Ocean currents 2. Pacific Ocean temperatures 3. Moored instrumentss  <b>b. Identifiers/Open-Ended Terms</b>   <b>c. COSATI Field/Group</b>			
<b>18. Availability Statement:</b> Approved for public release; distribution unlimited.		<b>19. Security Class (This Report)</b> Unclassified	<b>21. No. of Pages</b> 60
		<b>20. Security Class (This Page)</b> Unclassified	<b>22. Price</b>

WHOI-83-30

**A COMPILATION OF MOORED CURRENT METER DATA  
FROM THE WESTERN NORTH PACIFIC, VOLUME XXXI,  
1980 - 1982**

by

Ellen Levy and Susan A. Tarbell

**WOODS HOLE OCEANOGRAPHIC INSTITUTION**

Woods Hole, Massachusetts 02543

August 1983

**TECHNICAL REPORT**

*Prepared for the Office of Naval Research under contract N00014-76-C-0197;  
NR 083-400.*

*Reproduction in whole or in part is permitted for any purpose of the United  
States Government. This report should be cited as WHOI-83-30.*

*Approved for public release; distribution unlimited.*


Approved for Distribution:

*N. P. Fofonoff*

N. P. Fofonoff, Chairman  
Department of Physical Oceanography

ABSTRACT

Summaries of long-term current, temperature and pressure measurements from moored instruments in the western Pacific Ocean (along 152°E, between 28°N and 41°N) are presented. Tables, plots and statistics are presented for filtered and unfiltered time series. There were two consecutive settings of instruments, referred to as WesPac I and II, each spanning a one year interval (nominal). The objective of the experiment was to motivate exploratory descriptions of the low frequency variability in the western North Pacific.



AA

NOV 1967

## Contents

Abstract	i
Contents	ii
Diagram of Fiche	iii
Acknowledgments	iv
Preface	v
Presentation	1
Introduction	2
Array Location (Figure 1)	3
Mooring Numbers with Location (Table 1)	4
Instrumentation	6
Moorings	7
Mooring Depth and Topography (Figure 2)	8
Mooring Statistics (Table 2)	9-10
Mooring Configuration (Table 3)	11-14
Data Processing	16
Depth	17
Programs	18,23-24
Data Quality (Table 4)	19-20
Table of Statistics (Table 5)	21-22
References	25-26
Array Plots (Figure 3)	27-32
3-D Temperature Plots (Figure 4)	33-34
Time Series Plots (Figures 5-24)	35-54

## On Fiche

## Fiche # / Columns

Reproduction of Printed Pages		1	
Individual Data Displays	WesPac I	200 M	2 1-4
		500 M	2 5-14
		1200 M	3 1-8
		4000 M	4 1-10
		5000 M	4 11-14
Individual Data Displays	WesPac II	200 M	5 1-4
		500 M	5 6-12
		1200 M	6 1-10
		4000 M	7 1-9
		5000 M	7 11-14

Fiche 1

A						T E X T								
B														
C				500		1200			4000			3 - D Temp.		
D				VECTOR		ARRAY		PLOTS						
E			Composite Stick Plots											
F			Composite Temp. Plots											
G														
	1	2	3	4	5	6	7	8	9	10	11	12	13	14

Fiche 2 through 7

A													
B													
C													
D													
E													
F													
G													



ACKNOWLEDGMENTS

Many people share credit for the quality of data returned during the WesPac I and II experiment. They include the people in the buoy group instrument shop and those who worked on the moorings, both hardware and design. Jerry Dean updated the text concerning instrumentation. The officers and crews of the R. V. Thomas Washington and the R. V. Thomas Thompson deserve special mention for their willing assistance in mooring deployment and recovery. The principal investigator responsible for the moored instrument array was Dr. William J. Schmitz, Jr. Cooperative experiments included CTD and XBT observations, for which Dr. P. P. Niiler (Oregon State University) was responsible.

The experiment was funded at W.H.O.I. by the Office of Naval Research Contract N00014-76-C-0197, NR 083-400.

## PREFACE

This volume is the thirty-first in a series of Data Reports presenting moored current meter and associated data collected by the WHOI Buoy Group.

Volumes I-XVI present data prior to 1976 and are not listed below.

Volumes XVII through XXX present data obtained during the years 1972-1980, either by year or experiment (see notes).

A data directory and bibliography for the years 1963-1978 has been published, as WHOI Technical Report 79-88.

Volume XXXI presents data from the West Pacific Experiments, 1980-1982.

<u>Volume No.</u>	<u>WHOI Ref. No.</u>		<u>Notes Year Experiment</u>
XVII	78-49	Tarbell, S., A. Spencer and R. E. Payne	1975-1977 POLYMODE Array II
XVIII	79-65	Tarbell, S., M. G. Briscoe and R. A. Weller	1978 JASIN
XIX	79-34	Spencer, A., C. Mills and R. Payne	1974-1975 POLYMODE Array I
XX	79-56	Spencer, A.	1974 Rise Array
XXI	79-85	Mills, C. and P. Rhines.	1978 W.B.U.C.
XXII	79-87	Tarbell, S. and R. Payne.	1973 measurements
XXIII	80-40	Tarbell, S. and R. Payne.	1978 POLYMODE Array III
XXIV	80-41	Spencer, A. , K. O'Neill and J. R. Luyten	1976 INDEX
XXV	81-12	Spencer, A., E. D'Asaro and L. Armi	1977 B.B.L. Expt.
XXVI	81-45	Chausse, D. and R. Payne	1972 measurements
XXVII	81-68	McKee, T., E. Francis and N. Hogg	1975,78 topographic expts.
XXVIII	81-73	Mills, C., S. Tarbell, W. B. Owens and R. Payne	1978 L.D.E.
XXIX	82-16	Levy, E., A. Spencer, G. Needell, G. Hund, and J. R. Luyten	1979 INDEX
XXX	82-43	Levy, E., S. A. Tarbell, and N. P. Fofonoff	1979-1980 GSE/NSOI

## PRESENTATION

The printed portion of this report contains plots, introductory text and information about the instruments and data processing procedures. Tables and figures give information on moorings, instruments, and the quality of the data. Data are shown graphically in numerous composite displays. The data series are presented in a merged form of the two settings, whenever possible.

These pages are reproduced on microfiche (fiche) one. Fiche 2 through 7 contain standard displays of data from each individual instrument. Included are spectral plots, tables of statistics, variables versus time, histograms, progressive vector diagrams and scatter plots.

A generalized layout of the microfiche is shown on page iii. Each printed page is numbered at the top, with a fiche designation at the bottom.

## INTRODUCTION

WesPac I (Schmitz et al., 1982; Bradley, 1982) and II involved long-term settings of an exploratory moored array in the western North Pacific. This array is similar in goals and design to the POLYMODE Array II in the western North Atlantic (Schmitz, 1976, 1977, 1978). The emphasis was on long-term measurements, providing a more complete description of the low frequency variability in an energetic area in the western North Pacific.

An array of ten moorings including 38 current meters was deployed along 152°E longitude, between 28°N and 41°N latitude, for eleven months. The northernmost moorings were located in the vicinity of the Kuroshio Extension, more southern moorings in the Oyashio Frontal Region of recirculation and the southernmost mooring was located below the recirculation region in a "mid-ocean" area. These ten moorings were recovered and redeployed at the same locations in May 1981 for another thirteen months, and finally retrieved in May 1982. Instruments were located at standard nominal depths of 250, 500, 1200, 4000, 5000 meters. See Figure 1 and Table 1 for further details.

Cooperative investigations involving CTD and XBT observations were conducted (Niler, 1980; Schmitz et al., 1982). The data will not be presented in this report.




Figure 1: Array location (shown in rectangle) of the western Pacific experiment (WesPac I and II). The northernmost mooring location is WP01.

Table 1

MOORING NUMBERS AND NOMINAL LOCATIONS

<u>MOORING LOCATION</u>	<u>WesPac</u> #	<u>WHOI</u> <u>DATA</u> #	<u>WHOI</u> <u>DATA</u> #
152°E 41.00°N	WP01	6951 6952 6953 6954 6955	7281 7282 7283 7284 7285
152°E 39.00°N	WP02	6961 6962 6963	7271 7272 7273
152°E 37.50°N	WP03	6971 6972 6973	7261 7262 7263
152°E 36.25°N	WP04	6981 6982 6983	7251 7252 7253
152°E 35.00°N	WP05	6991 6992 6993 6994 6995	7241 7242 7243 7244 7245
152°E 33.75°N	WP06	7001 7002 7003	7221 7222 7223
152°E 32.50°N	WP07	7011 7012 7013 7014 7015	7211 7212 7213 7214 7215
152°E 31.25°N	WP08	7021 7022 7023	7201 7202 7203
152°E 30.00°N	WP09	7031 7032 7033	7191 7192 7193
152°E 28.00°N	WP10	7041 7042 7043 7044 7045	7181 7182 7183 7184 7185

(This page is left blank intentionally.)

## INSTRUMENTATION

### Current Meters

The moorings in both settings of the array were instrumented with burst sampling and vector averaging current meters. These Savonius rotor and vane instruments are coupled in-line on the moorings and provide a measure of the speed and direction of the currents and, with calibrated thermistor sensors, water temperature. A crystal controlled time reference, accurate to within one second per day is synchronized with UTC (Universel Temps Coordonné) before launch and the accrued error recorded after recovery.

The Model 850 current meter, originally built by Geodyne, measures in a burst sampling mode described by Webster (1968). These early instruments were extensively modified at WHOI in the mid 1970's to take advantage of newly developed low-power integrated-circuit technology and a new sensor bearing design. The basic burst sampling technique was not changed. At a pre-determined time interval, which can be set to any binary multiple of 7.5 minutes, the instrument turns on and logs the clock count and a measure of the temperature. It then samples the 5.19 second rotor count, compass position and vane position for a preset number of "strokes", either 5, 13 or 21. These data are recorded on magnetic tape. It then turns off until the beginning of the next record. Valdes (1977) includes a more detailed discussion of the WHOI COS/MOS 850 current meter. For these arrays, the stroke rate was set to 7 and the recording interval to 1 hour.

By the early 1970s, engineers at WHOI had developed a vector averaging current meter which is now commonly known as the VACM. Built by AMF Sea-Link Systems (now EG&G Sea-Link), the VACM continuously sums vector increments of water flow sensed by the rotor and vane. At regular intervals, usually 15 minutes, it then records, on a magnetic tape cassette, the accumulated east-west and north-south velocities as a part of the data record. McCullough (1975) discusses calibration of the vector averaging current meter and its recording technique.



Some VACMs average temperature over the entire recording interval to an accuracy of about  $0.01^{\circ}\text{C}$  (Payne et. al., 1976). By 1980, a modification had been developed which permitted up to four variables in addition to current data to be recorded in a time-shared or multiplexed (MX) mode. These MX-VACMs measure pressure in addition to temperature, each averaging over about one-half of the record interval. The multiplex circuit temperature measurement is accurate to about  $.006^{\circ}\text{C}$  and pressure is measured to about 0.1% or 3 decibars for a standard 3000 decibar transducer. Pressure and temperature sensors are recalibrated between deployments.

Two multiplex VACMs on Moored Station 724 measured inclination in addition to temperature and pressure, although the pressure transducer on the VACM at 4000 m. was over-range and no pressure data were obtained. The tilt sensors were electrolytic levels which produce an electronic signal proportional to tilt about a sensitive axis. Two components of tilt were thus measured in multiplex channels 3 and 4 and when combined with the instantaneous compass position give a qualitative measure of the magnitude and the direction of inclination ("tilt" and "tilt azimuth" respectively) of the instrument, thus the mooring, at that point.

## MOORINGS

Figure 2 shows the depths of the instruments on the moorings and the bottom topography. Table 2 summarizes the mooring statistics.

Details of mooring configuration are shown in Table 3. Mooring items are listed with their lengths measured in meters. Depths of the individual instruments are underlined. A pinger was placed on WP10, for both settings, as an engineering experiment.

The anchors, unless otherwise stated are 3000 lb. wet-weight cylinders. The item "glass balls and chain" refers to glass flotation spheres with hard hats, each one bolted to  $3/8"$  chain at one meter intervals. See Heinmiller (1976) for a more complete description of WHOI moorings.




Figure 2: Mooring configuration relative to the bottom topography.

Table 2

MOORING STATISTICSWesPac I

<u>WesPac</u> #	<u>FILE</u>	<u>DEPTH</u> (M)	<u>DATE SET</u> 1980	<u>DATE RET.</u> 1981	<u>LOCATION</u>	<u>BOTTOM</u> <u>DEPTH(M)</u>
WP01	6951	240	5 JUL	27 MAY	40 59.1 N 152 1.1 E	5278
	6952	490				
	6953	1190				
	6954	3990				
	6955	5077				
WP02	6961	495	5 JUL	25 MAY	38 58.3 N 152 4.0 E	5664
	6962	1195				
	6963	3995				
WP03	6971	501	6 JUL	24 MAY	37 30.1 N 152 1.8 E	5842
	6972	1201				
	6973	4001				
WP04	6981	507	8 JUL	23 MAY	36 17.8 N 152 2.5 E	5945
	6982	1207				
	6983	4007				
WP05	6991	261	9 JUL	21 MAY	34 58.8 N 152 1.9 E	6149
	6992	511				
	6993	1211				
	6994	4015				
	6995	5949				
WP06	7001	478	12 JUL	20 MAY	33 46.4 N 151 59.4 E	5952
	7001	1178				
	7003	3979				
WP07	7011	250	13 JUL	19 MAY	32 29.0 N 152 10.3 E	5728
	7012	500				
	7013	1200				
	7014	4000				
	7015	5540				
WP08	7021	506	14 JUL	17 MAY	31 16.0 N 152 4.7 E	5952
	7022	1206				
	7023	4006				
WP09	7031	494	15 JUL	16 MAY	30 2.1 N 152 0.8 E	5966
	7032	1194				
	7033	3994				
WP10	7041	251	17 JUL	14 MAY	27 59.6 N 151 56.4 E	6078
	7042	501				
	7043	1202				
	7044	3984				
	7045	5890				

Table 2 (continued)

MOORING STATISTICSWesPac II

<u>WesPac</u> <u>#</u>	<u>FILE</u>	<u>DEPTH</u> <u>(M)</u>	<u>DATE SET</u> <u>1981</u>	<u>DATE RET.</u> <u>1982</u>	<u>LOCATION</u>	<u>BOTTOM</u> <u>DEPTH (M)</u>
WP01	7281	287	28 MAY	4 JUN	41 2.33 N 152 1.08 E	5356
	7282	537				
	7283	1237				
	7284	4037				
	7285	5216				
WP02	7271	522	26 MAY	3 JUN	38 57.7 N 152 6.6 E	5680
	7272	1222				
	7273	4023				
WP03	7261	486	24 MAY	2 JUN	37 28.3 N 152 4.4 E	5828
	7262	1186				
	7263	3987				
WP04	7251	496	24 MAY	2 JUN	36 16.0 N 152 0.8 E	5938
	7252	1196				
	7253	3996				
WP05	7241	255	22 MAY	1 JUN	34 53.7 N 152 0.7 E	6158
	7242	505				
	7243	1204				
	7244	4004				
	7245	5958				
WP06	7221	498	20 MAY	31 MAY	33 49.75 N 151 59.37 E	5952
	7222	1198				
	7223	3999				
WP07	7211	265	19 MAY	30 MAY	32 28.14 N 152 6.62 E	5756
	7212	515				
	7213	1214				
	7214	4015				
	7215	5556				
WP08	7201	496	18 MAY	LOST	31 15.79 N 152 3.52 E	5931
	7202	1196				
	7203	3996				
WP09	7191	502	17 MAY	28 MAY	30 3.1 N 152 2.8 E	6005
	7192	1202				
	7193	4002				
WP10	7181	247	15 MAY	26 MAY	27 59.3 N 151 53.6 E	6057
	7182	497				
	7183	1198				
	7184	3984				
	7185	5856				

Table 3a.

MOORING CONFIGURATION

	<u>WesPac I</u>			
	<u>695</u>	<u>699</u>	<u>701</u>	<u>704</u>
Float/Radio/Light				
3/8" chain	2	10	2	2
17" glass balls	14		14	31
3/8" chain				3
3/16" wire	10		10	10
VACM-P	240	261	250	251
3/16" wire	<u>234</u>	<u>233</u>	<u>234</u>	<u>233</u>
17" glass balls	3	3	3	3
3/16" wire	10	10	10	10
VACM-P	490	511	500	501
3/16" wire	<u>682</u>	<u>679</u>	<u>682</u>	<u>679</u>
17" glass balls	3	4	3	4
3/16" wire	10	10	10	10
Pinger				1
VACM	1190	1211	1200	1202
3/16" wire	<u>750</u>	<u>761</u>	<u>750</u>	<u>773</u>
1/4" Kevlar				1082
3/16" wire	1000	1000	1000	
1/4" Kevlar				900
3/16" wire	1000	1000	1000	
17" glass balls	31	10	31	3
3/16" wire	10	10	10	10
VACM	<u>3990</u>	<u>4015</u>	<u>4000</u>	<u>3984</u>
1/4" Kevlar				500
3/16" wire	1000	1000	1000	
1/4" Kevlar				498
3/16" wire	50	294	500	
3/16" wire		500		124
3/16" wire		100		307
3/16" wire				297
3/16" wire				148
16" glass balls	26		26	19
17" glass balls		20		
3/8" chain	2		2	2
VACM	<u>5077</u>	<u>5949</u>	<u>5540</u>	<u>5890</u>
3/8" chain	<u>2</u>	<u>2</u>	<u>2</u>	<u>2</u>
Release				
1/2" chain	3	3	3	3
3/8" wire	162	162	162	162
3/4" nylon	20	20	10	10
1/2" chain	5	5	5	5
Anchor	<u>5278</u>	<u>6149</u>	<u>5728</u>	<u>6078*</u>

Table 3b.

MOORING CONFIGURATIONWesPac I (continued)

	<u>696</u>	<u>697</u>	<u>698</u>	<u>700</u>	<u>702</u>	<u>703</u>
Float/Radio/Light						
3/8" chain	2	3		2	2	2
17" glass balls	15	15	15	15	15	15
3/16" wire	10	10	10	10	10	10
VACM-P	495	501	507	478	506	494
3/16" wire	<u>679</u>	<u>679</u>	<u>679</u>	<u>679</u>	<u>679</u>	<u>679</u>
17" glass balls	6	6	6	6	6	6
3/16" wire	10	10	10	10	10	10
VACM	1195	1201	1207	1178	1206	1194
3/16" wire	<u>752</u>	<u>752</u>	<u>752</u>	<u>752</u>	<u>752</u>	<u>752</u>
3/16" wire					500	
3/16" wire	1000	1000	1000	1000	500	1000
3/16" wire	1000	1000	1000	1000	1000	1000
17" glass balls	28	28	28	28	28	28
3/16" wire	10	10	10	10	10	10
VACM	3995	4001	4007	3979	4006	3994
3/16" wire	<u>1000</u>	<u>1000</u>	<u>1000</u>	<u>1000</u>	<u>1000</u>	<u>1000</u>
3/16" wire					20	
3/16" wire					50	
3/16" wire	200	500	200	200	297	600
3/16" wire	200	50	679	500	446	100
3/16" wire		20			20	
3/16" wire					20	
3/16" wire	200	200		200	20	200
16" glass balls	23	24	24	24	23	24
17" glass balls				1	1	
Release						
1/2" chain	3	3	3	3	3	3
3/4" nylon	20	20	10	20	20	20
1/2" chain	5	5	5	5	5	5
Anchor	<u>5664</u>	<u>5842</u>	<u>5945</u>	<u>5952</u>	<u>5952</u>	<u>5966</u>

\* NOTE: The anchor on mooring 704 was a Stimson with a dry weight of 4100 lb.

Table 3c.

MOORING CONFIGURATIONWesPac II

	<u>718</u>	<u>721</u>	<u>724</u>	<u>728</u>
Float/Radio/Light				
3/8" chain	2	2	10	2
17" glass balls	34	14		14
3/16" wire	10	10		10
VACM-P	247	265	255	287
3/16" wire	232	234	233	234
17" glass balls	3	3	3	3
3/16" wire	10	10	10	10
VACM-P	497	515	505#	537
3/16" wire	679	682	679	682
17" glass balls				3
16" glass balls	4	3	4	
3/16" wire	10	10	10	10
Pinger	1			
850 CM	1198	1214	1204	1237
3/16" wire	773	750	750	751
3/16" wire			750	500
3/16" wire		1000	1000	500
1/4" Kevlar	1082			
1/4" Kevlar	900			
3/16" wire		1000	1000	500
3/16" wire				500
17" glass balls	3	31	10	31
1/4" wire	10	10	10	10
VACM-P	3984			4037
VACM		4015	4004#	
1/4" Kevlar	500			
3/16" wire			500	
1/4" Kevlar	498			
3/16" wire			500	
3/16" wire	10	1000	500	
3/16" wire	100	50	200	1000
3/16" wire	297	100	148	20
3/16" wire	307	300	20	20
3/16" wire	124	50	50	100
16" glass balls		26		
17" glass balls	19		20	26
3/8" chain	2	2		
VACM	5856	5556	5958	5216
3/8" chain	2	2	2	3
Release				
1/2" chain	3	3	3	3
3/4" nylon				47
1/4" wire	161	162	162	
3/4" nylon	20	20	20	
3/4" dacron				52
1/2" chain	5	5	5	5
Anchor	6057*	5756	6158	5356**

Table 3d.

MOORING CONFIGURATIONWesPac II (continued)

	<u>719</u>	<u>720</u>	<u>722</u>	<u>725</u>	<u>726</u>	<u>727</u>
Float/Radio/Light						
3/8" chain	2	2	2	2	2	2
17" glass balls	15	15	15	15	15	15
3/16" wire	10	10	10	10	10	10
VACM-P	502	496	498	496	486	522
3/16" wire	<u>679</u>	<u>679</u>	<u>679</u>	<u>679</u>	<u>679</u>	<u>679</u>
17" glass balls	6	6	6	6	6	6
3/16" wire	10	10	10	10	10	10
850 CM	<u>1202</u>	<u>1196</u>	<u>1198</u>	<u>1196</u>	<u>1186</u>	<u>1222</u>
3/16" wire	<u>752</u>	<u>752</u>	<u>752</u>	<u>752</u>	<u>752</u>	<u>752</u>
3/16" wire	1000	1000	1000	1000	1000	1000
3/16" wire	1000	1000	1000	1000	1000	1000
17" glass balls	28	28	28	28	28	28
1/4" wire	10	10	10	10	10	10
VACM	4002	3996	3999	3996	3987	4023
3/16" wire	<u>1000</u>	<u>500</u>	<u>1000</u>	<u>1000</u>	<u>1000</u>	<u>1000</u>
3/16" wire	200	500	300	50	500	200
3/16" wire	500	446	500	100	20	200
3/16" wire	50	297	10	700	50	50
3/16" wire	50	50	20	20	200	50
3/16" wire	100	20	50			100
3/16" wire	20	50				
3/16" wire	10					
17" glass balls		1	2			
16" glass balls	24	23	23	24	24	23
Release						
1/2" chain	3	3	3	3	3	3
3/4" nylon	20	20	20	20	20	10
1/2" chain	5	5	5	5	5	5
Anchor	<u>6005</u>	<u>5931</u>	<u>5952</u>	<u>5938</u>	<u>5828</u>	<u>5680</u>

# These instruments were modified to include inclinometers.

\* The anchor on mooring 718 was a Stimson with a wet weight of 3000 lb.

\*\* Mooring 728 had a modular anchor with wet weight of 2250 lb.



(This page is left blank intentionally.)

## DATA PROCESSING

After WesPac I was processed and before WesPac II was processed, WHOI converted to a new computer. This change demanded new programming, and produced a difference in the style of the output for the WesPac II data.

Data are identified by a mooring number, a sequential instrument position number (e.g., 6953 is the third instrument down on mooring 695), a letter to indicate the data version (e.g., 6953A is the first editing of 6953), and a number to indicate the time sampling interval for that data record (e.g., 6953A900 is the fifteen minute (900 seconds) averaged version).

As the time series from the two settings have been merged together, additional naming parameters have been used. The mooring locations for both settings were numbered 1 through 10, starting with the northernmost location and ending with the southernmost location. For example, WP01 refers to the combined time series of mooring 695 in WesPac I and mooring 728 in WesPac II.

Current meter data from cassettes (VACM) and cartridges (Model 850) were transcribed to 9-track magnetic tapes, converted to scientific units, edited to remove launch and retrieval transients and bad points, and linearly interpolated across missing or erroneous data cycles. All directional data has been processed and plotted in degrees true. Data quality was determined at this point, and is noted in Table 4.

There was a problem with directions in the data file 6992. The filtered version was heavily edited (86 out of 313 points) to make the areas where there were bad directions agree with adjacent data. The data quality of the edited filtered series is questionable. The data from the unfiltered series are considered bad and are not shown in the report.

Series 7181 had special editing. Due to a malfunction in the instrument, the vector components were unusable. East and north components were created from the last compass and vane value in each recording interval, together with the total rotor count for the interval.

Series 7185 showed a temperature off-set (as compared with the corresponding instrument for the first setting). No instrumental reason could be found, but CTD measurements in the area indicated the measurements to be too low. The data series was edited, by adding  $.024^{\circ}$  to each value. The original temperature is shown on the microfiche plots and tables, and the edited temperature is used for the composite display, on page 54.

Low passed versions of data series were formed by passing the data through a Gaussian filter with a 24 hour half-width, and then subsampling the filtered series once a day. The composite plots shown for each mooring use these filtered data series.

### Depth

Depths for the current meters were computed using a standard procedure. Before launch, water depth at the anticipated anchor location was read from a depth recorder at sea. The mooring components were adjusted to bring the instruments as close as possible to the nominal depths. The recorded lengths of all the mooring components became input for the program NOYFB (Moller, 1976). Instrument depths for zero current were calculated.

Mooring 695 (WesPac I) presented a problem. Calculated depths differed from believed actual depths, based on the records of the two pressure sensors on the mooring. Instrument 6951 believed to be at about 250 meters was actually closer to 600 meters according to the pressure records, and instrument 6952 was closer to 800 meters than the predicted 500 meters. Since these were the only two instruments with pressure recorders it is not known whether or not the lower instruments were also deeper than was predicted.

## PROGRAMS

### Variables versus Time

The stick plots, displayed on Fiche 2 through 7, Row F, are plotted so that North is up, relative to the time axis. The composite stick diagrams in Figures 5 through 24 are plotted such that East is up.

Individual variables and the stick plots are plotted against time from one day Gaussian filtered series.

Tilt and tilt azimuth for 7242 and 7244 are shown in Row G of Fiche 5 and 7.

### Statistics

Statistics are computed on the filtered and unfiltered time series. Mean, standard error, variance, kurtosis and extrema are computed. East and north covariance, correlation and other statistics are given for the vectors. For reference, note that a Gaussian random variable would have a kurtosis of three and a skewness of zero.

Statistical tables for the unfiltered velocity and temperature statistics are shown in Fiche 2 through 7, in Row B. Unfiltered pressure statistics are shown in Row G. Filtered statistics are found in Row D of Fiche 2 through 7 and Table 5 of the text.

See Volume XVII (POLYMODE Array II) of this series for a more detailed discussion of these parameters.

Table 4

DATA QUALITYWesPac I

<u>FILE</u>	<u>START DATE</u>	<u>END DATE</u>	<u>COMMENTS</u>
6951	80-VII-07	81-V-26	600m depth / good
6952	80-VII-07	80-X-19	800m depth / only 4 months data
6953			1.5 months data / not processed
6954	80-VII-07	81-V-26	good
6955	80-VII-07	81-V-26	good
6961	80-VII-07	81-V-24	good
6962	80-VII-07	81-V-24	good / very low speeds 22 Aug-4 Oct.
6963	80-VII-07	81-V-24	good
6971	80-VII-08	81-V-23	good
6972	80-VII-08	81-V-23	good
6973	80-VII-08	81-V-23	good
6981	80-VII-10	81-V-21	good
6982	80-VII-10	81-V-21	good
6983	80-VII-10	81-V-21	good
6991	80-VII-11	81-V-19	good
6992	80-VII-11	81-V-19	no compass values within 45° of 180°
6993	80-XI-24	81-V-19	data after 23 Nov looks good
6994	80-VII-11	81-V-19	good / recreated time base
6995	80-VII-11	81-V-19	temp. only / lost rotor during launch.
7001	80-VII-14	81-V-18	good
7002	80-VIII-23	81-V-18	2 gaps early in record / rest good
7003	80-VII-14	81-V-18	good
7011	80-VII-15	81-V-17	good
7012	80-VII-15	81-V-17	good
7013	80-VII-15	81-V-17	good
7014	80-VII-15	81-V-17	good
7015	80-VII-15	81-I-23	Temp. not good after Jan. Speed not good after Sept.
7021	80-VII-16	81-V-16	good
7022	80-VII-16	81-V-16	good
7023	80-VII-16	81-V-16	good
7031	80-VII-17	81-V-14	good
7032			when clock reads zero, so did temp., vane
7033	80-VII-17	81-V-14	good
7041	80-VII-19	81-V-12	good
7042	80-VII-19	81-V-12	good
7043	80-VII-19	81-V-12	good / speed seems low 29 Sep - 13 Oct
7044	80-VII-19	81-V-12	good
7045	80-VII-19	81-V-12	good

Table 4 (continued)

DATA QUALITYWesPac II

<u>FILE</u>	<u>START TIME</u>	<u>END TIME</u>	<u>COMMENTS</u>
7281	30-V-81	19-XI-81	short, tape motor drive malfunction
7282	30-V-81	03-VI-82	good
7283	30-V-81	03-VI-82	good
7284	30-V-81	02-VI-82	good
7285	30-V-81	03-VI-82	good
7271	28-V-81		instrument lost
7272	28-V-81	02-VI-82	3 months no speeds, middle of record
7273	28-V-81	02-VI-82	temp. only, no useful rotor
7261	26-V-81	01-VI-82	good
7262	13-VI-81	01-VI-82	good, short
7263	26-V-81	01-VI-82	good
7251	25-V-81	31-V-82	good
7252	25-V-81	31-V-82	good
7253	25-V-81	31-V-82	good
7241	24-V-81	30-V-82	good
7242	24-V-81	30-V-82	good
7243	24-V-81	30-V-82	good
7244	24-V-81	30-V-82	good
7245	24-V-81	30-V-82	good
7221	22-V-81	01-IX-82	rotor dies in August. temp, pres. good
7222	22-V-81	29-V-82	good, no temp.
7223			no data
7211	21-V-81	28-V-82	good
7212	25-IX-81	28-V-82	no rotor. good temp., press.
7213	21-V-81	28-V-82	good
7214	21-V-81	28-V-82	good
7215	21-V-81	28-V-82	good
7201			mooring lost
7202			lost
7203			lost
7191			no useful data
7192	19-V-81	26-V-82	good
7193	19-V-81	26-V-82	good
7181	17-V-81	24-V-82	pressure short, (see page 14 for component information)
7182	17-V-81	24-V-82	good
7183	17-V-81	24-V-82	good
7184	17-V-81	24-V-82	clock problem, two parts
7185	17-V-81	24-V-82	temperature offset (see page 14)

Table 5

## TABLE OF STATISTICS: velocity variables

SERIES	START DATE	# IN AVG.	MEANS		VARIANCES		CO-VARIANCE
			<U>	<V>	<UPRSQ>	<VPRSQ>	<UPRVPR>
7201B1DG24	81- V -30	174	6.3	-9.5	71.7	54.6	-32.0
NP01.600M	80-VII-07	697	4.1	-0.7	53.7	19.2	-6.7
7283B1DG24	81- V -30	370	2.7	-1.3	10.6	6.3	-0.5
NP01.4000M	80-VII-07	696	-1.0	-1.1	10.0	6.3	-1.3
NP01.5000M	80-VII-07	697	-0.6	-1.7	13.8	7.4	-2.0
6961A1DG24	80-VII-07	322	-2.6	0.3	60.7	44.2	-19.3
NP02.1200M	80-VII-07	395	-0.1	-0.1	22.5	7.0	-3.9
6963A1DG24	80-VII-07	322	2.9	-1.4	58.2	15.3	-10.4
NP03.500M	80-VII-08	694	-0.8	0.8	61.8	93.7	-10.3
NP03.1200M	80-VII-08	693	-1.6	1.2	22.2	23.1	-0.3
NP03.4000M	80-VII-08	694	-1.9	1.5	32.1	20.3	-8.5
NP04.500M	80-VII-10	691	5.3	-6.3	211.1	190.2	-96.7
NP04.1200M	80-VII-10	691	0.2	-1.4	49.2	41.5	-23.1
NP04.4000M	80-VII-10	691	-1.7	2.3	19.1	20.9	-4.9
NP05.200M	80-VII-11	689	14.3	-17.6	647.0	954.8	-238.7
NP05.500M	80-VII-11	689	3.4	-10.1	271.1	343.2	-95.5
7243B1DG24	81- V -24	372	4.4	-4.3	52.3	93.9	-27.5
NP05.4000M	80-VII-11	689	-2.7	-0.7	40.2	49.7	-19.1
7245B1DG24	81- V -24	372	-1.3	-1.6	40.3	38.2	-19.6
NP06.500M	80-VII-14	415	-5.6	-1.8	245.1	406.0	-21.1
NP06.1200M	80-VIII-23	644	3.6	-0.5	58.3	56.2	16.7
7003A1DG24	80-VII-14	309	0.8	0.6	19.0	43.4	6.7
NP07.200M	80-VII-15	683	-2.2	-4.0	416.1	470.5	27.2
7012A1DG24	80-VII-15	307	5.2	-1.9	116.0	161.4	41.2
NP07.1200M	80-VII-15	683	-1.9	0.6	27.6	17.8	1.6
NP07.4000M	80-VII-15	683	-2.0	2.1	16.8	17.4	6.0
7215B1DG24	81- V -21	373	-3.0	3.7	32.3	39.7	11.6
7021A1DG24	80-VII-16	305	5.2	-10.0	158.6	131.3	50.0
7022A1DG24	80-VII-16	305	1.5	-1.4	20.9	11.3	6.4
7023B1DG24	80-VII-16	305	1.4	0.5	17.3	13.0	8.3
7031A1DG24	80-VII-17	302	1.0	-1.0	65.1	43.7	-18.1
7192B1DG24	81- V -19	373	-1.8	0.5	18.2	8.1	-1.5
NP09.4000M	80-VII-17	679	-1.3	-0.5	13.7	10.6	2.0
NP10.200M	80-VII-19	675	-1.8	-0.9	87.0	69.0	9.7
NP10.500M	80-VII-19	675	-1.2	-0.2	36.5	22.9	-1.0
NP10.1200M	80-VII-19	675	-0.2	0.7	5.6	3.9	-1.3
NP10.4000M	80-VII-19	527	0.1	1.2	15.4	11.2	-3.1
NP10.5000M	80-VII-19	675	-1.3	1.5	20.0	16.3	-7.0

Table 5 (continued)

## TABLE OF STATISTICS: temperature and pressure

SERIES	# IN AVG.	MEAN <T>	STD.DEV. SQRT<TPRSS>	TEMP/VEL.COVAR. <UPRTPR><VPRTPR>		MEAN <P>	STD.DEV SQRT<PPR>
7261810G24	174	4.061	0.903	-0.515	-0.344		
NP01.000M	697	3.920	0.286	0.054	0.223	591.0	23.6
7263810G24	370	2.531	0.074	0.034	0.065		
NP01.4000M	696	1.462	0.006	0.000	0.000		
NP01.5000M	697	1.530	0.005	0.002	0.001		
6961A10G24	322	4.402	0.272	0.174	0.653		
NP02.1200M	395	2.582	0.054	0.029	-0.023		
6963A10G24	322	1.475	0.006	0.002	-0.007		
NP03.500M	694	4.733	0.456	-0.102	-0.248	540.6	23.6
NP03.1200M	693	2.645	0.105	0.003	-0.014		
NP03.4000M	694	1.465	0.007	0.009	-0.014		
NP04.500M	691	4.993	0.746	3.895	-2.580	572.6	52.2
NP04.1200M	691	2.648	0.099	0.130	-0.215		
NP04.4000M	691	1.472	0.007	0.005	-0.012		
NP05.200M	689	12.258	3.591	6.582	-27.250	361.9	61.9
NP05.500M	689	7.180	2.653	-2.654	-3.397	613.8	61.6
7243810G24	372	2.837	0.231	0.516	-0.933		
NP05.4000M	689	1.484	0.010	0.033	-0.027		
7245810G24	372	1.603	0.003	0.007	-0.006		
NP06.500M	415	8.861	3.099	1.019	-17.668	566.3	68.3
NP06.1200M	644	3.382	0.426	1.460	-0.060		
7003A10G24	309	1.473	0.009	0.004	0.028		
NP07.200M	683	13.434	2.761	-9.540	-4.165		
7012A10G24	307	6.564	2.345	-8.226	-1.999	645.6	68.3
NP07.1200M	683	2.915	0.277	-0.570	-0.094		
NP07.4000M	683	1.458	0.010	-0.016	-0.010		
7315810G24	373	1.534	0.006	-0.005	-0.005		
7021A10G24	305	10.099	2.218	-6.436	6.245	556.3	35.4
7022A10G24	305	3.029	0.181	-0.321	0.073		
7023810G24	305	1.462	0.009	0.012	0.013		
7031A10G24	302	10.444	0.649	0.058	0.734	569.9	2.4
7192810G24	373	3.133	0.099	0.018	-0.040		
NP09.4000M	679	1.478	0.009	-0.013	-0.004		
NP10.200M	675	16.414	0.282	-0.653	-0.214		
NP10.500M	675	11.637	0.527	-0.829	-0.542	508.3	9.6
NP10.1200M	675	3.221	0.117	-0.019	-0.012		
NP10.4000M	527	1.477	0.006	0.002	0.000		
NP10.5000M	675	1.535	0.004	-0.005	0.002		



### Histograms

The variables temperature, velocity components, speed and direction are shown as frequency of occurrence versus amplitude plots. They are shown in Row C of Fiche 2 through 7. The mean for each data series is marked for WesPac I. The direction of histogram 7181 is questionable due to an instrument malfunction. See page 14 for further information.

### Progressive Vector and Scatter Plots

Progressive vector plots are based on the unfiltered time series. The current vectors are placed tail-to-head so as to show the path that a perfect particle in a perfectly homogeneous flow would have travelled. Flow regimes and low frequency behavior show up well on this type of plot. The plot begins with an asterisk, the first day of each month is marked with a triangle and every month is annotated.

Every daily averaged point from the series is plotted in a scatter plot, in which east and north components are plotted as points on a polar diagram. The line drawn through the points is the principal axis. This line measures the orientation angle but does not denote the length of the major axis. It has slope  $\theta$  (where  $\theta$  is given by  $\tan(2\theta) = (2\overline{UV}) / (\overline{u^2} - \overline{v^2})$ ) and it passes through the point  $(\overline{U}, \overline{V})$ .

Progressive vectors and scatter plots are shown in Row E of Fiche 2 through 7.

### Spectra

The horizontal kinetic energy (HKE) and temperature are displayed as spectra (Hunt, 1977). The HKE spectrum is half of the sum of the spectra of the east and north components. It has the advantage of not being tied to a particular coordinate system. These plots are shown in the fiche.

The HKE, temperature, and pressure spectra have units of either  $(\text{cm}^2/\text{sec}^2)/\text{cph}$ ,  $(^\circ\text{C})^2/\text{cph}$ , and  $(\text{Decibars})^2/\text{cph}$  respectively. The spectra are all one-sided, i.e., the area under the spectrum is equal to the variance of the original record. The plots are log-log rather than "variance preserving", i.e., the contributions of various frequency bands to the total variance are not in proportion to the displayed areas. They are shown on Fiche 2 through 7 in Row B, for velocities and temperatures, and Row G for pressure.

### Array Plots

Five day Gaussian filtered data series are subsampled every five days and plotted, according to their location, as velocity vectors for each depth. Plots are shown in Figure 3.

### Three Dimensional Temperature Plots

These displays show temperature as a function of time and space. Each surface consists of temperature values at the depth indicated. Geographical position (latitude) is shown along the Y axis and the X axis denotes time in days. The data series have been passed through a five day half-width Gaussian filter, and a point is plotted every fifth day. These plots are shown in Figure 4.

REFERENCES

- Bradley, K. F., 1982. Technical activities associated with an exploratory array in the western North Pacific. Woods Hole Oceano. Inst. Tech. Rept. WHOI-82-41.
- Heinmiller, R. H., 1976, Woods Hole Buoy Project Moorings, 1960-1974. Woods Hole Oceano. Inst. Tech. Rept. WHOI-76-53.
- Hunt, M., 1977, A program for spectral analysis of time series. WHOI Technical Memorandum 2-77.
- McCullough, J. R. (1975). Vector Averaging Current Meter Speed Calibration and Recording Technique. Woods Hole Oceano. Inst. Tech. Rept. WHOI-75-44.
- Moller, D. A., 1976, A computer program for the design and static analysis of single-point subsurface mooring systems: NOYFB. Woods Hole Oceano. Inst. Tech. Rept. WHOI-76-59.
- Niiler, P. P., 1980, CTD transect of the Kuroshio Extension, 28-41° N, 152°E. Scripps Ref. 81-3 (Technical Report).
- Payne, R. E., A. L. Bradshaw, J. P. Dean and K. E. Schleicher, 1976, Accuracy of temperature measurements with the V.A.C.M. Woods Hole Oceano. Inst. Tech. Rept. WHOI 76-94.
- Schmitz, W. J., Jr., 1976, Eddy kinetic energy in the deep western North Atlantic, J. Geophys. Res., 81, 4981-4982.

REFERENCES (continued)


- Schmitz, W. J., Jr., 1977, On the deep general circulation in the western North Atlantic., J. Mar. Res., 35, 21-28.
- Schmitz, W. J., Jr., 1978, Observations of the vertical structure of low frequency fluctuations in the western North Atlantic, J. Mar. Res., 36, 295-310.
- Schmitz, W. J., Jr., P. P. Niiler, R. L. Bernstein, and W. R. Holland, 1982. Recent long-term moored instrument observations in the western North Pacific. J. Geophys. Res., 87, 9425-9440.
- Tarbell, S. A., A. Spencer, and R. E. Payne, 1978, A compilation of moored current meter data and associated oceanographic observations, Vol. XVII (Polymode Array II data). Woods Hole Oceano. Inst. Tech. Rept. WHOI-78-49.
- Valdes, J. R. (1977). COS/MOS 850 Current Meter Report. Woods Hole Oceano. Inst. Tech. Rept. WHOI-77-30.
- Webster, F. (1968). A Scheme for Sampling Deep-Sea Currents from Moored Buoys. Woods Hole Oceano. Inst. Tech. Rept. WHOI-68-2.

## WESPAC 1 500M. 5-DAY CURRENT VECTORS



Figure 3a

## WESPAC 2 500M. 5-DAY CURRENT VECTORS



1 5 CM/SEC I 1 DEG OF LAT. I 1 DEG OF LONG.

LOWER LEFT CORNER OF FRAME 148 W 28 N

Figure 3b

1-C-5

## WESPAC 1 1200M. 5-DAY CURRENT VECTORS





Figure 3c

## WESPAC 2 1200M. 5-DAY CURRENT VECTORS



I 5 CM/SEC I 1 DEG OF LAT. I 1 DEG OF LONG

LOWER LEFT CORNER OF FRAME 148 W 28 N

Figure 3d



## WESPAC 1 4000M. 5-DAY CURRENT VECTORS




I 5 CM/SEC I 1 DEG OF LAT. I 1 DEG OF LONG.

LOWER LEFT CORNER OF FRAME 148 W 28 N

Figure 3e

## WESPAC 2 4000M. 5-DAY CURRENT VECTORS



I 5 CM/SEC I 1 DEG OF LAT. I 1 DEG OF LONG

LOWER LEFT CORNER OF FRAME 148 W 28 N

Figure 3f

1-C-11




Figure 4a




Figure 4b




Figure 5




Figure 6

## MOORING WP02 CURRENT VECTORS EAST IS UP




Figure 7




Figure 8



## MOORING WP03 CURRENT VECTORS EAST IS UP




Figure 9

## MOORING WP03 TEMPERATURES / PRESSURES




Figure 10

## MOORING WP04 CURRENT VECTORS EAST IS UP




Figure 11




Figure 12




Figure 13




Figure 14

## MOORING WP06 CURRENT VECTORS EAST IS UP




Figure 15




Figure 16






Figure 17




Figure 18

## MOORING WP08 CURRENT VECTORS EAST IS UP




Figure 19




Figure 20

## MOORING WP09 CURRENT VECTORS EAST IS UP




Figure 21




Figure 22




Figure 23




Figure 24



## MANDATORY DISTRIBUTION LIST

FOR UNCLASSIFIED TECHNICAL REPORTS, REPRINTS, AND FINAL REPORTS  
PUBLISHED BY OCEANOGRAPHIC CONTRACTORS OF THE OCEAN SCIENCE  
AND TECHNOLOGY DIVISION OF THE OFFICE OF NAVAL RESEARCH

(Revised October 1983)

- 1 Deputy Under Secretary of Defense  
(Research and Advanced Technology)  
Military Assistant for Environmental Science  
Room 3D129  
Washington, DC 20301

Office of Naval Research  
800 North Quincy Street  
Arlington, VA 22217

- 3 Attn: (Code applicable to Program) \*  
1 Attn: Code 420C  
2 Attn: Code 102C

Commanding Officer  
Naval Research Laboratory  
Washington, DC 20375

- 6 Attn: Library Code 2627  
1 Attn: Library Code 2620, Mr. Peter Imhof

- 12 Defense Technical Information Center  
Cameron Station  
Alexandria, VA 22314  
Attn: DCA

Commander  
Naval Oceanographic Office  
NSTL Station  
Bay St. Louis, MS 39522

- 1 Attn: Code 8100  
1 Attn: Code 6000  
1 Attn: Code 3300

- 1 NODC/NOAA  
Code D781  
Wisconsin Avenue, N.W.  
Washington, DC 20235

\* Applicable Codes: 422 (PO); 422CB (Chem/Bio); 422CS (Coastal); 425 (G&G); 425AR (Arctic);  
421 (OE); 421SP (Ships); 425OA (Ocean Acoustics); 425UA (Underwater Acoustics)

END

FILMED

11-83

DTIC